

UNIVERSAL® Flow Monitors

FlowStream® Mass Flowmeters for Gases

TYPICAL APPLICATIONS

- Blanketing
- Sparging/Purging Gases
- Burner Management
- Assist Gases
- Leak Tests
- Injectable Gases
- Shielding Gas
- Gas Consumption
- Gas Blending
- Gas Chromatography

Features

Meter types

- Output options: current, voltage, frequency, and scaled pulse
- Battery operated
- Bi-directional
- Programmable set points
- Open collector outputs
- Intrinsically safe for hazardous location use - CSA and CE

Selectable options for installed units

- Gas measured (for Multigas units)
- Response time (5 or 50 ms)
- Open collector set point flow rates
- Range of electrical output
- Visual readout of flow rate or total, pressure and temperature

FlowStream®



General Description

Laminar Flow Element differential pressure flowmeters are good for clean, dry, non-corrosive, non-condensing gasses. Corrected for temperature and pressure, it has a mass flow output. The EMI immunity and fast response (5 ms available) make the meters suitable for robotics' applications (painting or welding). A variety of outputs are available (4-20 mA, 0-5 V, and pulse). NIST traceable and CSA units are Type 4 weatherproof. The accuracy is a uniform 1% of full scale subject to limitations described in the Specifications section.

Units with a display can indicate flow rate or total as well as gas temperature and pressure.



Battery operated units are offered. Calibration is done on air with empirically derived conversion factors. Oxygen cleaning optional.

Sizes range from 1/4 to 3/4 inch NPT. Anodized aluminum is the standard material for the meter body and 316 Stainless Steel is available for use where external corrosion is a factor.

Dimensions of OFS/OFM Series

Approximate in inches (mm)

Flow Rate Maximum	"H" Height Overall	"C" Height to Port	"P" Port Connections
120 SCFH	2.34" [59mm]	0.68" [17mm]	1/4-18 NPT
280 SCFH	2.59" [66mm]	0.93" [24mm]	1/4-18 NPT
520 SCFH	2.98" [76mm]	0.55" [14mm]	3/8-18 NPT
1000 SCFH	3.79" [96mm]	1.09" [28mm]	1/2-14 NPT
1000 SLPM	4.63" [118mm]	1.51" [38mm]	3/4-14 NPT



General Instrument Specifications

Flow Ranges:	500 SCCM full scale to 1,000 SLPM full scale, 1 SCFH full scale to 2,100 SCFH full scale
Turndown Ratio:	100:1
Maximum Operating Pressure:	100 PSIG
Burst Pressure:	200 PSIG
Pressure Effect on Accuracy:	Less than 0.03% full scale / PSI (See <i>Note 1</i>)
Maximum Operating Temperature:	176 °F (80 °C)
Minimum Operating Temperature:	-13 °F (-25 °C)
Temperature Effect on Accuracy:	Less than 0.03% full scale / °F
Maximum Pressure Drop:	Normal 2 PSI, Max 3.5 PSI (Individually listed under Multigas Flow Selection chart by port size and flow rate)
Process Connections:	1/4"-3/8"-1/2"-3/4" Available in NPT, BSPT, BSPP and SAE
Wetted Parts	
Sensors:	Glass-filled nylon, alumina-based ceramic, silicon, gold, epoxy
Flow Body Internals:	Anodized aluminum or 300 series stainless steel, Viton® or buna n seals
Enclosure Rating:	Type 4
Display:	4-digit LCD digital display, 0.35" high
Approvals:	CE, CSA, Intrinsic Safety (all classes and divisions) with proper zener barrier.

Note 1: Most of the error at high pressures is due to sensor offset shifts. Accuracy can be improved by re-zeroing the meter at operating pressure or calibrating at the specific pressure.

Electrical Specifications

Accuracy (Including Linearity and Repeatability)	
Flow:	± 1% of full-scale for flowmeters sized from 15-566 SLPM (31-1200 SCFH) of Air ± 2% of full-scale for flowmeters sized for lower than 15 SLPM (30 SCFH) of Air ± 2% of full-scale for flowmeters sized for higher than 566 SLPM (1201 SCFH) of Air
Pressure:	± 1 PSI (See <i>Note 2</i>)
Temperature:	± 3 °F
Totalizer:	± 0.25% of full-scale (in addition to flow accuracy)
Output Signal	
Analog:	4-20 mA (2-wire loop powered) 0-5 V, 0-10 V, 1-5 V, 2-10 V 0-5 V Bi-directional (2.5 V = 0 flow)
Frequency:	0-1000 Hz, 200-1200 Hz 0-3V signal amplitude
Pulse:	1,250-5,000 pulses/minute, user selectable 0-3V pulse amplitude 2 msec pulse width
Response Time:	user selectable 5 msec or 50 msec (to 63% of step change) for analog outputs, 50 msec (to 63% of step change) for frequency and pulse outputs
Alarms:	2 independent open-collector outputs (high/low flow rate) with corresponding LEDs Open-Collector Rating 30VDC at 50 mA
Electrical Connection:	4- or 7-conductor shielded cable with pigtail
Supply Voltage:	10-30 VDC is standard 12-24 VDC for Intrinsically Safe 7.2-9 VDC for battery-operated units (See <i>Note 3</i>)
Supply Current:	22 mA @ F.S. flow (includes over-range) for 4-20 mA loop-powered transmitters 5 mA for voltage, frequency, and pulse outputs 3.5 mA for battery-operated units (See <i>Note 3</i>)

Note 2: Pressure, temperature, and totalizer are only displayed on the LCD. No output signal is available for these parameters.

Note 3: Battery-operated units require a standard 9V alkaline battery and will operate for over 100 hours continuously. An On/Off switch allows the user to turn the power off, thus conserving the battery life. These flowmeters have no output signal.

How To Order Flowstream for a Single Gas

Select the appropriate symbols to build a model code:

Example: OFS - E F - 3 A - 200 SLPM - T - X 1B - D10

SERIES = OFS

MATERIAL FOR METER BODY

Anodized Aluminum = E
316 Stainless Steel = I

SEALS

® = F
Buna N = B

THREAD TYPE FOR THREADED PORT

N = NPT
T = SAE
B = BSPT
P = BSPP

GAS						
Air	Argon	CO ₂	Helium	Hydrogen	Methane	Oxygen
= A	= R	= CO2	= HE	= H	= M	= O2

PIPE SIZE in Inches

1/4	= 2
3/8	= 3
1/2	= 4
3/4	= 6

MAXIMUM FLOW IN SLPM

128	107	64	116	256	107	116
*228	190	114	208	457	190	208
548	457	274	498	1096	457	498
1000	833	500	909	1999	833	909

MAXIMUM FLOW IN SCFH

280	233	140	255	560	233	255
500	417	250	455	1000	417	455
1200	1000	600	1091	2400	1000	1091
2188	1824	1094	1989	4377	1824	1989

NOTE: Lowest maximum flow rates are 50 SCCM and 1 SCFH respectively.

* NOTE: The flows selected in each size must be less than or equal to the maximum.

OUTPUT

Digital Visual Display with Output

- X 1A = 4-20mA
- X 1B = 4-20mA with 2 alarms
- X 2A = 4-20mA Intrinsically Safe
- X 4A = 0-5 VDC
- X 4B = 0-5 VDC with 2 alarms
- X 5A = 0-10 VDC
- X 5B = 0-10 VDC with 2 alarms
- X 12A = 1-5 VDC
- X 12B = 1-5 VDC with 2 alarms
- X 14A = 2-10 VDC
- X 14B = 2-10 VDC with 2 alarms
- X 19A = 0-1000 HZ
- X 20A = 200-1200 HZ
- X 22A = pulse out (rate varies with size)
- X 30A = 0-5 VDC (bi-directional flow)
- X 40A = visual readout only (battery powered)

No Visual Display with Output

- Z 1A = 4-20mA
- Z 2A = 4-20mA Intrinsically Safe
- Z 4A = 0-5 VDC
- Z 5A = 0-10 VDC
- Z 12A = 1-5 VDC
- Z 14A = 2-10 VDC
- Z 19A = 0-1000 HZ
- Z 20A = 200-1200 HZ
- Z 22A = pulse out (rate varies with size)
- Z 30A = 0-5 VDC (bi-directional flow)

SPECIAL OPTIONS

CLEAN FOR OXYGEN SERVICE = C1

10 FOOT CABLE = D10

VACUUM USE (7.35 to 14.7PSIA) = ZVAC

NOTE: Also good for use at normal pressures